

Materials Safety Data Sheet.

No. 1907/2006 (REACH)

Revision: 14.02.2019 (GB) Version 1.6

Traxx Seal/Seal Plus

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Name of product	Traxx Seal/Seal Plus
Manufacturer/distributor	Traxx Construction Products Unit 4/1 Rocklea Drive, Port Melbourne, Victoria 3207 Phone: 03 9646 9200
Advice	Technical Department Phone: 03 9646 9200
Recommended intended purpose(s)	Impregnator

2. HAZARDS IDENTIFICATION

Classification

R10
Xi; R36/38
N; R51/53
Xn; R65

R-phrases

10 Flammable.
36/38 Irritating to eyes and skin.
51/53 Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.
65 Harmful: may cause lung damage if swallowed.
67 Vapours may cause drowsiness and dizziness.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characterization

Solvent based Impregnator

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification
123-86-4	204-658-1	n-butyl acetate	<15	R10; R66; R67
64742-82-1	265-185-4	Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha	>25	Xn R65
		Anionic surfactants	<10	Xi R 38-41

Additional advice

Benzene <0,1 %; RL67/548, Annex I, H, P, 4

Traxx Construction Products Pty Ltd

Unit 4/1 Rocklea Drive, Port Melbourne, Victoria 3207, Australia

T +61 (0) 3 9646 9200 | F +61 (0) 3 9645 6942 | E sales@traxxcp.com.au

please visit www.traxxcp.com.au



Materials Safety Data Sheet.

No. 1907/2006 (REACH)

Revision: 14.02.2019 (GB) Version 1.6

Traxx Seal/Seal Plus

4. FIRST AID MEASURES

General Information

Remove contaminated soaked clothing immediately.

In case of inhalation

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin, wash off immediately with soap and water.

In case of eye contact

In case of contact with eyes, rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

Do not induce vomiting

If swallowed by mistake, drink plenty of water and seek medical treatment.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Foam

Dry Powder

Carbon Dioxide

Sand

Extinguishing media which must not be used for safety reasons

Full water jet

Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

Dangerous gases possible in the case of fire formation.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Ensure adequate ventilation.

Use personal protective clothing.

Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Methods for cleaning up

Take up with absorbent material (e.g. sand, sawdust, general-purpose binder).

Traxx Construction Products Pty Ltd

Unit 4/1 Rocklea Drive, Port Melbourne, Victoria 3207, Australia

T +61 (0) 3 9646 9200 | F +61 (0) 3 9645 6942 | E sales@traxxcp.com.au

please visit www.traxxcp.com.au



Materials Safety Data Sheet.

No. 1907/2006 (REACH)

Revision: 14.02.2019 (GB) Version 1.

Traxx Seal/Seal Plus

7. HANDLING AND STORAGE

Advice on safe handling

Use only in thoroughly ventilated areas.
Use solvent resistant equipment.
Take the usual precautions when handling chemicals.

Advice on protection against fire and explosion

Keep away from sources of ignition – No smoking.
Take precautionary measures against static discharges.

Further information on storage conditions

Keep container dry, tightly closed and store in a cool and aired place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection

Breathing apparatus in the event of high concentrations.
Short term: filter apparatus, filter A

Hand protection

Chemical-resistant gloves

Eye protection

Safety goggles

General protective measures

Avoid contact with eyes and skin

Hygiene measures

At work do not eat, drink and smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form

Liquid

Colour

Colourless, Clear

Odour

Aromatic

Important health, safety and environmental information

	Value	Temperature	At	Method	Remark
pH value in delivery state	Not applicable				
Starts to boil	>130°C				
Flash point	>21°C				
Lower explosion limit	Ca. 0,6 Vol-%				
Upper explosion limit	Ca. 8 Vol-%				
Density	Ca. 0,8 g/cm ³				
Solubility in water					More or less insoluble
Viscosity 1 Outflow time	<30 s			ISO 2431/3 mm	

Traxx Construction Products Pty Ltd

Unit 4/1 Rocklea Drive, Port Melbourne, Victoria 3207, Australia

T +61 (0) 3 9646 9200 | F +61 (0) 3 9645 6942 | E sales@traxxcp.com.au

please visit www.traxxcp.com.au



Materials Safety Data Sheet.

No. 1907/2006 (REACH)

Revision: 14.02.2019 (GB) Version 1.6

Traxx Seal/Seal Plus

10. STABILITY AND REACTIVITY

Conditions to avoid

No hazardous reactions known.

11. TOXOLOGICAL INFORMATION

Acute toxicity/irritability/sensitization

	Value/Validation	Species	Method	Remark
LD 50 acute oral	Not determined			
LD 50 acute dermal	Not determined			
LC 50 acute inhalation	Not determined			

12. ECOLOGICAL INFORMATION

Data on elimination (persistence and degradability)

	Elimination rate	Method of analysis	Method	Validation
Physico-chemical degradability	Not determined			
Biological degradability	Not determined			

13. DISPOSAL CONSIDERATIONS

Waste code No.

07 01 04*

Name of waste

other organic solvents, washing liquids and mother liquors

Wastes marked with an asterick are considered to be hazardous waste pursuant to Directive 91/689/EEC on hazardous waste.

Recommendations for the product

In accordance with regulations for special waste, must be taken to a special waste disposal.

Recommendation for packaging

Totally emptied packaging may be taken for recycling.

14. TRANSPORT INFORMATION!

! Land and inland navigation transport ADR/RID

UN 1993 Flammable liquid, n.o.s. (White spirit), 3, III

Marine transport IMDG

UN 1993 Flammable liquid, n.o.s. (White spirit), 3, III

Air transport ICAO/IATA-DGR

UN 1993 Flammable liquid, n.o.s. (White spirit), 3, III

Traxx Construction Products Pty Ltd

Unit 4/1 Rocklea Drive, Port Melbourne, Victoria 3207, Australia

T +61 (0) 3 9646 9200 | F +61 (0) 3 9645 6942 | E sales@traxxcp.com.au

please visit www.traxxcp.com.au



Materials Safety Data Sheet.

No. 1907/2006 (REACH)

Revision: 14.02.2019 (GB) Version 1.6

Traxx Seal/Seal Plus

15. REGULATORY INFORMATION!

Remarks for classification

The product is classified and labelled in accordance with EC directives.

Classification

Xn Harmful

N Dangerous for the environment

R-phrases

10 Flammable.

36/38 Irritating to eyes and skin.

51/53 Toxic to aquatic organisms, may cause adverse long-term effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

67 Vapours may cause drowsiness and dizziness.

S-phrases

2 Keep out of the reach of children.

23.3 Do not breathe vapour.

24 Avoid contact with skin.

62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Hazardous ingredients for labeling

Naphtha (petroleum), hydrodesulphurized heavy

National regulations

Water hazard class 2 VwVwS (17.05.1999)

16. OTHER INFORMATION!

Further information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Wording of the R-phrases specified in chapter 2 (not the classification of the formulation)

R 10 Flammable.

R 38 Irritating to skin.

R 41 Risk of serious damage to eyes.

R 65 Harmful: may cause lung damage if swallowed.

R 66 Repeated exposure may cause skin dryness or cracking.

R 67 Vapours may cause drowsiness and dizziness.

Traxx Construction Products Pty Ltd

Unit 4/1 Rocklea Drive, Port Melbourne, Victoria 3207, Australia

T +61 (0) 3 9646 9200 | F +61 (0) 3 9645 6942 | E sales@traxxcp.com.au

please visit www.traxxcp.com.au

