

# SLURRY FILTER PRESS

## for concrete sludge

Environmental protection in the construction sector is becoming increasingly important. Clients demand from service providers ecological answers regarding the disposal of sludge that results from concrete drilling and sawing. Added to this is the conservation of resources through reusability of the filtered cooling water. The chamber filter press meets the high requirements in a special way.

### Advantages

- Easy handling of the function
- Clean working in a sensitive environment
- High flexibility due to compact design and low weight
- Robust chassis with pneumatic tires (suitable for construction sites)
- Dry sludge cake can be disposed of via building materials recycling

TECHNICAL DATA	
<i>The press can be easily divided into 2 parts</i>	
CHAMBER NO.	4 (optional 5)
CHAMBER VOLUME	4.7 L (with 5 chambers 5.9 L)
AIR PRESSURE	6-7 bar
RECYCLING CAPACITY	up to 600 L/h
PRESS	47 Kg (without chambers)
CARRIAGE	19 Kg
WEIGHT	92 Kg (complete)
DIMENSIONS	822 x 682 x 1155 mm (without handle)



### TRAXX CONSTRUCTION PRODUCTS

Unit 4/1 Rocklea Drive, Port Melbourne, Victoria, Australia 3207

**Phone:** 1300 109 108 | **Telephone:** +61 (0)3 9646 9200 |

**Email:** info@traxxcp.com.au | **Website:** www.traxxcp.com.au

