



PS1  
PORTABLE VACUUM LIFTING SYSTEM

VACUWORX PORTABLE VACUUM LIFTING SYSTEMS offer the perfect solution for smaller lifting challenges on the job or in the shop. Engineered for both interior and exterior applications, these battery powered lifters can go to work anywhere! The PS 1 can lift up to 800 Kg (1,700 lb / 0.8 tonne).

FEATURES

- Lightweight and completely portable
- Ideal for applications where no power source is available
- PS 1 is powered by a 12V 22 Ah rechargeable battery with integrated charging system
- Designed for manual use with the Lift Dolly or in conjunction with small host equipment such as mini skid steers, mini excavators, forklifts and small cranes

Includes 3m (10') vacuum hose, battery and battery charger (pad not included)



Technical Data	
Lift Capacity	800 Kg (1,700 lb / 0.8 tonne)
Dimensions	L362 x H165 x W292 mm
Weight	11 Kg (25 lb)



SL2  
SUBCOMPACT VACUUM LIFTING SYSTEM

THE SL 2 SUBCOMPACT VACUUM LIFTING SYSTEM is the ultimate attachment — lightweight and extremely versatile, the system has been updated with an improved hydraulic systems and modular pads to work with more machines and for more applications! Featuring all-aluminum construction, the patent pending design runs off the host machine's hydraulic system and can be easily attached in minutes to lift steel plate, saw-cut concrete, granite and marble slabs, landscape pavers and more! In addition, quick-connect hydraulic hoses make switching between attachments fast and easy so you can maximize productivity on the job. Perfect for floor, sidewalk, driveway, road and landscaping projects.

FEATURES

- Available with manual or wireless remote control
- Models with innovative accumulator design allow contractors to use the system on equipment without a case drain
- Hydraulically driven vacuum pump operates using the auxiliary hydraulics from the host machine (Minimum 10 GPM required with maximum 3,000 PSI)
- Includes quick-connect hydraulic hoses and factory pre-set flow control valve to ensure optimal performance
- Universal mounting plates allow easy attachment to all skid steer models
- All system components are fabricated from high quality aluminum to maximize overall lifting capacity of the host machine
- Designed to lift concrete, marble, granite, metal, steel, iron and landscape pavers
- Connects to small excavators, backhoes and cranes using clevis hook connection



Technical Data	
Lift Capacity	2000 Kg (4400 lb / 2 tonne)
Dimensions	L 584 x H 635 x W 737 mm
Weight	57 Kg

